



2315-K Bearing 2D drawings and 3D CAD models

**CONSOLIDATED BEARING 2315-K Self  
Aligning Ball Bearings**

Bearing No. 2315-K

|                         |   |
|-------------------------|---|
| Category                | Self Aligning Ball Bearings   |
| Inventory               | 0.0   |
| Manufacturer Name       | CONSOLIDATED BEARING  |
| Minimum Buy Quantity    | N/A   |
| Weight                  | 5.2   |
| EAN                     | 0644075114417   |
| Product Group           | B00152  |
| Mounting Method         | Tapered Adapter   |
| Enclosure               | Open  |
| Rolling Element         | Ball Bearing  |
| Adapter Sleeve          | H-2315  |
| Cage Material           | Steel   |
| Precision Class         | ABEC 1   ISO P0   |
| Internal Clearance      | C0-Medium   |
| Number of Rows of Balls | Double Row  |
| Other Features          | Allowable Misalignment 4 Deg   1:12 Taper   |
| Long Description        | 75MM Bore; Tapered Adapter Mount; 160MM Outside Diameter; 55MM Inner Race Width; 55MM Outer Race Width; Open; Steel Cage; Double Row of Balls; ABEC 1   ISO P0; C0-Medium |
| Inch - Metric           | Metric  |
| Category                | Self Aligning Ball Bearings   |
|                         |   |



## Machinery Parts Industry Co., Ltd.

|                          |   |
|--------------------------|---|
| UNSPSC                   | 31171532  |
| Harmonized Tariff Code   | 8482.10.50.68   |
| Noun                     | Bearing   |
| Keyword String           | Self Aligning   |
| Manufacturer URL         | <a href="http://www.consbrgs.com">http://www.consbrgs.com</a> |
| Manufacturer Item Number | 2315-K  |
| Weight / LBS             | 11.442  |
| d                        | 2.953 Inch   75 Millimeter                                    |
| D                        | 6.299 Inch   160 Millimeter                                   |
| Outer Race Width         | 2.165 Inch   55 Millimeter                                    |
| Inner Race Width         | 2.165 Inch   55 Millimeter                                    |